CLAIMS

What is claimed is:

1. A method comprising:

receiving a configuration for a user interface of an application;

determining a set of parameters corresponding to the configuration; and

dynamically generating user interface display code based upon the set of configuration

parameters.

2. The method of claim 1 further comprising:

transmitting the user interface display code to a client digital processing system in

response to a request to access the application.

3. The method of claim 1 wherein the configuration for the user interface is determined by

selecting one or more objects and positioning each object in a desired location of a free-form grid

layout.

4. The method of claim 2 wherein the request is communicated through the Internet and the

user interface display code is hyper text markup language code.

5. The method of claim 1 wherein the one or more objects are selected using a user input

device and each selected object is positioned by dragging the object to a desired location of the

free-form grid layout.

Page 16 of 22 005306.P107

Express Mail No.: EV 305340865 US

- 6. The method of claim 1 wherein positioning an object in a desired location of a free-form grid layout includes indicating a desired size for the object.
- 7. The method of claim 1 wherein indicating a desired size for the object includes selecting a perimeter of the object at a first location on the free-form grid layout and dragging the perimeter to a second location on the free-form grid layout.
- 8. The method of claim 4 wherein the hyper text markup language code is dynamically generated based upon the set of configuration parameters and based upon an origin of the request.
- 9. The method of claim 1 wherein the free-form grid layout comprises a plurality of grid cells and the set of parameters includes information indicating the position of each object in reference to one or more of the plurality of grid cells.
- 10. The method of claim 9 wherein the set of parameters includes a grid coordinate specifying one of the plurality of grid cells, a column span specifying a first dimension, and a row span specifying a second dimension for each of the one or more objects.

11. A system comprising:

a server digital processing system having a storage, the storage containing a set of configuration parameters corresponding to a configuration of a user interface of an application;

Patent Application 080403/(TAV:elc)

Page 17 of 22

005306.P107 Express Mail No.: EV 305340865 US one or more client digital processing systems coupled to the server digital processing

system capable of requesting access to the application such that the request causes the server

digital processing system to dynamically generate user interface display code based upon the set

of configuration parameters.

12. The system of claim 11 wherein the client digital processing system is coupled to the

server digital processing system through the Internet and the user interface display code is hyper

text markup language code.

13. The system of claim 11 wherein the configuration is determined by selecting one or more

objects and positioning each object in a desired location of a free-form grid layout.

14. The system of claim 11 wherein positioning an object in a desired location of a free-form

grid layout includes indicating a desired size for the object.

15. The system of claim 11 wherein indicating a desired size for the object includes selecting

a perimeter of the object at a first location on the free-form grid layout and dragging the

perimeter to a second location on the free-form grid layout.

16. The system of claim 14 wherein the hyper text markup language code is dynamically

generated based upon the set of configuration parameters and based upon an origin of the

request.

17. The system of claim 11 wherein the free-form grid layout comprises a plurality of grid

Patent Application 080403/(TAV:elc)

Page 18 of 22

005306.P107

Express Mail No.: EV 305340865 US

cells and the set of parameters includes information indicating the position of each object in reference to one or more of the plurality of grid cells.

- 18. The system of claim 17 wherein the set of parameters includes a grid coordinate specifying one of the plurality of grid cells, a column span specifying a first dimension, and a row span specifying a second dimension for each of the one or more objects.
- 19. A machine-readable medium that provides instructions, which when executed by a processing system, cause the processing system to perform a method comprising:

accessing a generic layout file for a user interface of an application, the generic layout file having a free-form grid layout and a set of objects;

creating a configuration for a user interface of an application;

determining a set of parameters corresponding to the configuration; and

dynamically generating user interface display code based upon the set of configuration

parameters.

- 20. The machine-readable medium of claim 19 further comprising:

 transmitting the user interface display code to a client digital processing system in response to a request to access the application.
- 21. The machine-readable medium of claim 19 wherein the configuration for the user interface is determined by selecting one or more objects and positioning each object in a desired location of a free-form grid layout.

Patent Application 080403/(TAV:elc)

Page 19 of 22

005306.P107 Express Mail No.: EV 305340865 US

- 22. The machine-readable medium of claim 20 wherein the request is communicated through the Internet and the user interface display code is hyper text markup language code.
- 23. The machine-readable medium of claim 19 wherein the one or more objects are selected using a user input device and each selected object is positioned by dragging the object to a desired location of the free-form grid layout.
- 24. The machine-readable medium of claim 19 wherein positioning an object in a desired location of a free-form grid layout includes indicating a desired size for the object.
- 25. The machine-readable medium of claim 19 wherein indicating a desired size for the object includes selecting a perimeter of the object at a first location on the free-form grid layout and dragging the perimeter to a second location on the free-form grid layout.
- 26. The machine-readable medium of claim 22 wherein the hyper text markup language code is dynamically generated based upon the set of configuration parameters and based upon an origin of the request.
- 27. The machine-readable medium of claim 19 wherein the free-form grid layout comprises a plurality of grid cells and the set of parameters includes information indicating the position of each object in reference to one or more of the plurality of grid cells.

Patent Application 080403/(TAV:elc)

Page 20 of 22

005306.P107

Express Mail No.: EV 305340865 US

28. The machine-readable medium of claim 27 wherein the set of parameters includes a grid coordinate specifying one of the plurality of grid cells, a column span specifying a first dimension, and a row span specifying a second dimension for each of the one or more objects.

Patent Application 080403/(TAV:elc)

Page 21 of 22

005306.P107 Express Mail No.: EV 305340865 US